

THROUGHOUT THE HOUSTON AREA WHICH MAY BE USED AS ALTERNATES TO FLIGHT WITHIN THE ESTABLISHED CLASS B AIRSPACE. ITS GROUND REFERENCES PROVIDE A GUIDE FOR IMPROVED VISUAL NAVIGATION. THIS IS NOT INTENDED TO DISCOURAGE REQUESTS FOR VFR OPERATIONS WITHIN THE CLASS B AIRSPACE BUT IS DESIGNED SOLELY FOR INFORMATION AND PLANNING PURPOSES.

CAUTION

THE ENTIRE HOUSTON AREA IS HEAVILY CONGESTED WITH MANY DIFFERENT AIRCRAFT TYPES. THESE ROUTE SUGGESTIONS ARE NOT STERILE OF OTHER TRAFFIC: THEY ARE AREAS WE BELIEVE LEAST CONGESTED IN AN AREA OF HEAVY CONGESTION. PILOT ADHERENCE TO VFR RULES MUST BE EXERCISED AT ALL TIMES. COMMUNICATIONS MUST BE MAINTAINED BETWEEN AIRCRAFT AND CONTROL TOWERS WHILE IN CLASS D AIRSPACE.

HOUSTON CHARTED VFR FLYWAY PLANNING CHART NOT TO BE USED FOR NAVIGATION **LEGEND**

Paved Runways AIRPORTS Unpaved Runways NAME (NAM) NAME (NAM) NAME (NAM)

VOR • DLG <u>138.8</u> NDB

NAVIGATIONAL AIDS VORTAC VOR-DME PPS 121.8 NDB-DME O DCW 262

• KIP 110.7

AIRSPACE INFORMATION

CLASS B AIRSPACE EXAMPLES OF CLASS B AIRSPACE ALTITUDES 70 --- CEILING IN HUNDREDS OF FEET MSL - FLOOR IN HUNDREDS OF FEET MSL

MODE C (SEE F.A.R. 91.215/AIM.)

CLASS C AIRSPACE MODE C (SEE F.A.R. 91.215/AIM

SPECIAL USE AIRSPACE Prohibited. Restricted, and Warning

SUGGESTED VFR

▶ IFR DEPARTURE ROUTES

IFR ARRIVAL ROUTES NAVIGATION REFERENCE POINT **OBSTRUCTIONS**

Example: MONUMENT

OPERATING RULES AND PILOT/EQUIPMENT REQUIREMENTS. Regardless of weather conditions, an ATC authorization is required prior to operating within the Class B Airspace. Pilots should not request an authorization to operate within the Class B Airspace unless the requirements of FAR 91.215 and FAR 91.31 are met. Included

on may take off or land a civil aircraft at an airport within the Class B Air

A transponder with automatic altitude reporting equipment. 5. A transponder with automatic anatorie reporting equipment.
NOTE: ATC may, upon notification, immediately authorize a deviation from the altitude reporting equipment requirement or for a transponder failure; however, other requests for deviations from the transponder equipment requirement must be submitted to the controlling ATC facility at least one hour before the proposed operation.

FLIGHT PROCEDURES

IFR FLIGHTS – Aircraft operating within the Houston Class B Airspace must be operated in accordance with ATC clearances and instructions. VFR FLIGHTS 1. Arriving alroraft should contact the appropriate approach control on specified frequencies and in relation to geographic fixes shown on the accompanying chart. Although arriving aircraft may be operating beneath the floor of the Class B Airspace on initial contact, communications should be established with approach control in relation to the points indicated for sequencing and spacing

purposes.

2. Aircraft departing the primary airports are requested to advise clearance delivery prior to taxling of their intended altitude and direction of flight to depart the Class B Airspace. Aircraft departing from other than the primary airports whose route of flight would penetrate the Class B Airspace should give this information to ATC on the appropriate frequencies.

3. Aircraft desiring to transit the Class B Airspace must obtain an ATC clearance to enter the Class B Airspace and will be handled on an ATC workload permitting basis.

ATC PROCEDURES

All aircraft will be controlled and separated while operating within the Class B Airspace, except helicopters need not be separated from other helicopters. Although radar separation will be the primary standard used, approved visual and other nonradar procedures will be applied as required or deemed appropriate. Traffic information on observed but unidentified radar targets will be provided on a workload permitting basis to aircraft operating outside the Class B Airspace.

NOTE: Assignment of radar headings and/or altitudes is based on the provision that a pilot operating in accordance with visual flight rules is expected to advise ATC if compliance with an assigned route, radar heading or altitude will cause the pilot to violate such rules.

- MILITARY TRAINING ROUTES (MTRs) -

All IR and VR MTRs are shown, and may extend from the surface upwards. Only the route centerline, direction of flight along the route and the route designator are depicted - route widths and altitudes are not shown. Since these routes are subject to change every 56 days, and the charts are reissued every 6 months, you are cautioned and advised to contact the nearest FSS for route dimensions and current status for those routes affecting your flight Routes with a change in the alignment of the charted route centerline will be indicated in the Aeronautical Chart Bulletin of the Airport/Facility Directory. DoD users refer to Area Planning AP/1B Military Training Routes North and South America for current routes.



